

Gazelle Outside-Back Replacement Instructions

Gazelle Outside-Back Replacement Instructions

Cautions: Removing the seat outside-back has a tendency to open up the gripper holes. Care must be taken to prevent over-working these gripper holes to help ensure the new outside-back grippers will not fit too loosely allowing the new outside-back to come off.

Care must be taken to ensure all new grippers line up with the existing holes prior to pressing the new back onto the seat to avoid breaking off any grippers.

Care must be taken as some outside-backs may be pinned which could result in scrapes or cuts if contact is made with these nails.



Photo A

1. Using an upholstery tool (*pictured above*), starting at the bottom, carefully work around the perimeter of the outside back working it away from the seat back (*Photo A*).
 - a. The welt is attached to the outside back – ensure your upholstery tool is inserted between the welt and the inside back.
 - b. Several passes around the outside may be required to loosen the back enough to remove.
 - c. Some fabrics have been “pinned” with braid nails for extra support. This will require additional work to remove seat backs that have been pinned.

GARY  PLATT

PERFORMANCE CASINO SEATING
RENO, NEVADA

4643 Aircenter Circle, Reno, Nevada 89502-5948
Toll-Free Phone: (800) 969-0999 • Toll-Free Fax: (800) 757-0788
Local Phone: (775) 824-0999 • Local Fax: (775) 824-824-0998

5-Prong Hi-Lo Seat Assembly Seat Removal Instructions

page 2 of 4



Photo B



Photo C

2. Fully inspect the chair back and remove any splinters, nails, or other foreign objects that might interfere with installation of the new outside back.
3. Using the upholstery tool, line up all 11 grippers with the existing holes ensuring the grippers are centered in each individual hole (Photo's B & C).
4. Using your fist or a soft rubber mallet, carefully tap around the perimeter of the seat back seating all 11 grippers fully into the seat back gripper holes.
5. For coarse fabrics such as Sherpa's or Shire's, additional nailing (pinning) to help secure the outside back may be added.

For additional support and/or service please contact your local Gary Platt Manufacturing representative.

DISCLAIMER: The content of this document and/or any Gary Platt Manufacturing (GPM) web-site content (www.garyplatt.com), including all information, data, communications, editorial content, photos, graphics, drawings, and in general any materials and services provided herein, is the property of GPM and is protected by the applicable copyright laws.

Furthermore, suppliers MUST strictly follow any and all instructions or damage to the property and/or injury may occur.

GARY PLATT

PERFORMANCE CASINO SEATING

RENO, NEVADA

4643 Aircenter Circle, Reno, Nevada 89502-5948

Toll-Free Phone: (800) 969-0999 • Toll-Free Fax: (800) 757-0788

Local Phone: (775) 824-0999 • Local Fax: (775) 824-824-0998